

DEVELOP

Dynamic balance

www.develop.eu



ineo 4020i



- > Black & white
A4 multifunctional
- > Up to 40 ppm

Option diagram

1 Media Input

Paper tray
PF-P23

Paper tray
PF-P24



2 Media output

Convenience stapler
EH-C591

legend

- Mandatory option
- Option
- This option can only be installed with the respective option above it

Finishing functionalities



Duplex



Corner stapling
(offline)

Description

Media Input

PF-P23 Paper tray	250 sheets; A5–A4; 60–120 g/m ²
PF-P24 Paper tray	520 sheets; A5–A4; 60–120 g/m ²

Media output

EH-C591 Convenience stapler	20-sheet off-line stapling
-----------------------------	----------------------------

Technical specifications

SYSTEM SPECIFICATIONS

Panel size/resolution	3.7"
System memory (standard/max)	256 MB (standard/max)
Interface	10/100/1,000-Base-T Ethernet; USB 2.0; Wi-Fi 802.11 b/g/n
Network protocols	TCP/IP (IPv4/IPv6); LPD; IPP; SNMP; HTTP; HTTP(S)
Automatic Document Feeder	Up to 50 originals; A6–A4; 64–90 g/m ² ; ADF
Paper input capacity (standard/max)	300 sheets / 1,340 sheets (standard/max)
Paper Tray 1	1x 250 sheets; A6–A4; 60–120 g/m ²
opt. Paper Tray 1 - Total	1x 250 sheets; A5–A4; 60–120 g/m ² (up to 2x)
opt. Paper Tray 2 - Total	1x 520 sheets; A5–A4; 60–120 g/m ² (up to 2x)
Manual bypass	50 sheets; A6–A4; custom sizes; 60–200 g/m ²
Automatic duplexing	A4; 60–105 g/m ²
Output Capacity (standard)	150
Copy/print volume (monthly)	Rec. 5,000 pages; Max. 100,000 pages
Toner lifetime	Black up to 12,000 pages
Imaging unit lifetime	50,000
Power consumption	220–240 V / 50/60 Hz; Less than 645 W
System dimension (W x D x H)	435 x 427 x 486 mm (without options)
System weight	Approx. 16.8 kg (without options)

PRINTER SPECIFICATIONS

Print resolution	1,200 x 1,200 dpi
Page description language	PCL 6 (XL3.0); PostScript 3; XPS
Operating Systems	Windows 7 (32/64); Windows 8.1 (32/64); Windows 10 (32/64); Windows Server 2008 (32/64); Windows Server 2008 R2; Windows Server 2012; Windows Server 2012 R2; Windows Server 2016; Windows Server 2019; Macintosh OS X 10.10 or later; Linux
Printer fonts	85 PCL Latin; 66 PostScript 3 Emulation Latin
Mobile Printing	Mopria (Android); Google Cloud Print; WiFi Direct

SCANNER SPECIFICATIONS

Scan speed - simplex	Up to 24/20 ipm in simplex
Scan resolution	1,200 x 1,200 dpi
Scan modes	Scan-to-eMail (Scan-to-Me); Scan-to-FTP; Scan-to-USB; TWAIN scan; WIA scan
File formats	JPEG; TIFF; PDF; XPS; PDF/A
Scan destinations	LDAP support

COPIER SPECIFICATIONS

Imaging technology	Laser
Toner technology	Polymerized Toner
Copy/print speed A4 (mono/colour)	Up to 40 ppm
Autoduplex Speed A4 (mono/colour)	Up to 20 ppm
1st copy out time A4 (mono/colour)	9.2 sec.
Warm-up time	Approx. 27 sec.
Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1–999
Original format	A6–A4
Magnification	25–400% in 1% steps; Auto-zooming

FAX SPECIFICATIONS

Fax standard	Super G3
Fax transmission	Analogue; i-Fax
Fax compression	MH; MR; MMR; JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	299 destinations + 20 groups

SYSTEM FEATURES

Security Functions (standard)	SSL2; SSL3 and TLS1.0/1.1/1.2 network communication; IPsec support; IEEE 802.1x support; Secure print; Kerberos
Accounting Functions (standard)	Active Directory support (user name + password + e-mail + smb folder)
Software	Net Care Device Manager; Web Connection; Driver Packaging Utility



DEVELOP

Konica Minolta Business Solutions Europe GmbH
 Europaallee 17 30855 Langenhagen Germany Phone +49 511 7404-0 www.develop.eu

- All specifications refer to A4-size paper of 80 g/m² quality.
- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of A4). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- DEVELOP and ineo are registered trademarks/product titles owned by Konica Minolta Business Solutions Europe GmbH.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.